

PVC Insulated material

Style UL1265 Hook-up Wire

Internal wiring of Appliances; or where exposed to oil at a temperature not exceeding 90°C
Whichever is applicable, The most popular hookup wire for Electric.

Description:

Conductor material of tinned or bare copper
Rated temperature 90 °C
Rated Voltage 600 V (Spark voltage 6000 V)
Flame resistance VW-1 and FT1
RoHS Compliant

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
2	259	26	.2854	7.25	.4114	10.45	0.1641	0.5384	231.00	343.68
4	133	25	.2386	6.06	.3646	9.26	0.2608	0.8559	168.77	251.10
6	266	30	.1882	4.78	.3142	7.98	0.4148	1.361	113.16	168.36

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available