

Silicone /Glass Braid Insulated material

Style UL3075 Hook-up Wire

Internal wiring of appliances or electric clothes, dryers where exposed to temperature not exceeding 200 °C

Description:

Conductor material of Tinned, Nickel or Silvered copper
“*” Conductor material used only Nickel or Silvered copper per ASTM B3/33
Rated temperature 200 °C
Rated Voltage 600 V (Spark voltage 6000 V)
Flame resistance FT2
RoHS Compliant
Covering for fiberglass braid

Specification:

| Gauge (AWG) | Number of Strands | Gauge of Strands (AWG) | Nom. Dia. of Stranded Conductor | | Nom. Fin. Wire Diam. | | Max. Resistance (dc at 20°C) Ohm/per | | Nom. Wt. | |
|-------------|-------------------|------------------------|---------------------------------|------|----------------------|------|--------------------------------------|------|---------------|-------|
| | | | Inch | mm | Inch | mm | 1000-ft | Km | LBS./1000 ft. | Kg/Km |
| 10 | 19 | 23 | .1209 | 3.07 | .2272 | 5.77 | 1.08 | 3.55 | 62.66 | 93.23 |
| *10 | 105 | 30 | .1181 | 3.00 | .2244 | 5.70 | 1.08 | 3.55 | 60.80 | 90.46 |

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available