

Silicone /Glass Braid Insulated material

Style UL3128 Hook-up Wire

Internal wiring of appliances or electric clothes, dryers where exposed to temperature not exceeding 150°C

Description:

Conductor material of Tinned or bare copper
Rated temperature 150 °C
Rated Voltage 600 V (Spark voltage 6000 V)
Flame resistance FT2
RoHS Compliant
Covering for fiberglass braid

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
4/0	259	21	.5197	13.20	.6890	17.50	0.0525	0.1722	715.06	1063.87
3/0	259	22	.4610	11.71	.6303	16.01	0.0669	0.2194	573.99	853.98
2/0	259	23	.4173	10.60	.5866	14.90	0.0814	0.2670	478.56	712.01
1/0	259	24	.3657	9.29	.5350	13.59	0.1026	0.3367	378.33	562.88
1	259	25	.3331	8.46	.5024	12.76	0.1300	0.4268	320.34	476.59

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available