

# Silicone /Glass Braid Insulated material

## Style UL3101 Hook-up Wire

Internal wiring of appliances or electric clothes, dryers where exposed to temperature not exceeding 150°C

### Description:

Conductor material of Tinned or bare copper  
Rated temperature 150 °C  
Rated Voltage 600 V (Spark voltage 6000 V)  
Flame resistance FT2  
RoHS Compliant  
Covering for fiberglass braid

### Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per		Nom. Wt.	
			Inch	mm	Inch	mm	1000-ft	Km	LBS./1000 ft.	Kg/Km
10	105	30	.1181	3.00	.2244	5.70	1.08	3.55	49.09	73.03

### Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available