

ETFE (TEFLON) Insulated material

Style UL1516 Hook-up Wire

Internal wiring of Appliances or electronic equipment

Description:

Conductor material of Tinned or Bare copper

Rated temperature 105 °C

Rated voltage 30 V (Spark voltage 1500V)

Flame resistance VW-1 or FT1

RoHS Compliant

Specification:

Gauge (AWG)	Number of Strands	Gauge of Strands (AWG)	Nom. Dia. of Stranded Conductor		Nom. Fin. Wire Diam.		Max. Resistance (dc at 20°C) Ohm/per	
			Inch	mm	Inch	mm	1000-ft	Km
10	19	23	.1205	3.06	.1283	3.26	1.08	3.54
12	19	25	.0929	2.36	.1008	2.56	1.72	5.64
14	19	27	.0728	1.85	.0807	2.05	2.73	8.96
16	19	29	.0591	1.50	.0669	1.70	4.45	14.6
18	1	18	.0402	1.02	.0480	1.22	6.77	22.2
18	7	26	.0465	1.18	.0543	1.38	7.07	23.2
18	19	31	.0465	1.18	.0543	1.38	7.07	23.2
20	1	20	.0320	0.81	.0398	1.01	10.73	35.2
20	7	29	.0374	0.95	.0453	1.15	11.19	36.7
20	19	33	.0374	0.95	.0453	1.15	11.19	36.7
22	1	22	.0252	0.64	.0335	0.85	17.20	56.4
22	7	30	.0299	0.76	.0378	0.96	18.11	59.4
22	19	35	.0299	0.76	.0378	0.96	18.11	59.4
24	1	24	.0201	0.51	.0280	0.71	27.23	89.3
24	7	32	.0236	0.60	.0315	0.80	28.72	94.2
24	19	36	.0236	0.60	.0315	0.80	28.72	94.2
26	7	34	.0189	0.48	.0268	0.68	45.73	150
28	1	28	.0126	0.32	.0205	0.52	69.21	227
28	7	36	.0150	0.38	.0228	0.58	72.87	239
30	1	30	.0100	0.25	.0177	0.45	110	361

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4

- Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available

