

XLPE Insulated material

Style UL3423 Hook-up Wire

Description:

Conductor: Tinned /Bare copper
Temperature Rating 125 °C
Rated voltage 300V
Flame resistance FT2
RoHS Compliant

Specification:

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Nom.	Tole.
3423	16	26/0.254	14.60	1.50	0.40	0.33	2.30	±0.10
	18	16/0.254	23.20	1.17	0.40	0.33	1.95	±0.10
	20	21/0.18	36.70	0.95	0.40	0.33	1.75	±0.10
	22	17/0.16	59.40	0.76	0.40	0.33	1.56	±0.10
	24	11/0.16	94.20	0.61	0.40	0.33	1.41	±0.10
	26	7/0.16	150.00	0.48	0.40	0.33	1.28	±0.10
	28	7/0.127	239.00	0.38	0.40	0.33	1.18	±0.10
	30	7/0.10	381.00	0.30	0.40	0.33	1.10	±0.10

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 - Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com