

XLETFE Insulated material

Style UL3557 Hook-up Wire

Description:

Conductor structure: Bare copper / tin plating / nickel plating / silver plating

Temperature Rating 200 °C

Voltage Rating 600V

Flame resistance VW-1

RoHS Compliant

Specification:

STYLE	stand ard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom	Min	Mon	Tol
3557	14	19/0.374	8.96	1.73	0.20	0.18	2.13	±0.10

OD of single strand 0.5mm±0.005mm, OD of single strand 0.5mm±0.01mm.

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 - Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com