

XLPE + XLPVDF Insulated material

Style UL3584 Hook-up Wire

Description:

Conductor: Tinned /Bare copper
Covering materials: XLPVDF covering
Temperature Rating 125 °C
Voltage Rating 600V
Flame resistance FT2
RoHS Compliant

Specification:

STYLE	standard AWG	Conduct or size (No./mm)	Conduct or resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		jacket thickness (mm)		Overall diameter (mm)	
					Nom	Min	Nom	Min	Nom	Tole.
3584	14	19/0.374	8.96	1.88	0.30	0.10	0.20	0.05	2.90	±0.15
	16	19/0.287	14.60	1.45	0.13	0.10	0.08	0.05	1.87	±0.10
	18	19/0.235	23.20	1.18	0.13	0.10	0.08	0.05	1.60	±0.10
	20	19/0.19	36.70	0.95	0.13	0.10	0.08	0.05	1.37	±0.10
	22	19/0.15	59.40	0.76	0.13	0.10	0.08	0.05	1.18	±0.10
	24	7/0.20	94.20	0.61	0.13	0.10	0.08	0.05	1.03	±0.10
	26	7/0.16	150.00	0.49	0.13	0.10	0.08	0.05	0.91	±0.10
	28	7/0.127	239.00	0.39	0.13	0.10	0.08	0.05	0.81	±0.10

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com