

EPDM Insulated material

Style UL3280 Hook-up Wire

Description:

Conductor: Tinned /Bare copper ;
Insulation materials: EPDM Insulation
Rated temperature: 150°C Rated voltage 300V
Flame resistance : FT2
RoHS Compliant

Specification:

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Min	Max
3280	14	41/0.254	8.96	1.88	0.76	0.68	3.40	±0.10
	16	26/0.254	14.60	1.50	0.76	0.68	3.05	±0.10
	18	16/0.254	23.20	1.17	0.76	0.68	2.75	±0.10
	20	21/0.18	36.70	0.95	0.76	0.68	2.50	±0.10
	22	17/0.16	59.40	0.76	0.76	0.68	2.25	±0.10
	24	11/0.16	94.20	0.61	0.76	0.68	2.10	±0.10
	26	7/0.16	150.00	0.48	0.76	0.68	2.00	±0.10

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4
- Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com