

EPDM Insulated material

Style UL3284 Hook-up Wire

Description:

Conductor: Tinned /Bare copper ;
Insulation materials: EPDM Insulation
Rated temperature: 125°C Rated voltage 600V
Flame resistance : FT2
RoHS Compliant

Specification:

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Min	Max
3284	08	168/0.254	2.23	3.80	1.52	1.37	6.84	±0.20
	10	105/0.254	3.54	3.00	1.15	1.04	5.30	±0.15
	12	65/0.254	5.64	2.36	1.15	1.04	4.66	±0.15
	14	41/0.254	8.96	1.88	1.15	1.04	4.18	±0.15
	16	26/0.254	14.60	1.50	1.15	1.04	3.80	±0.15
	18	16/0.254	23.20	1.17	1.15	1.04	3.48	±0.10
	20	21/0.18	36.70	0.95	1.15	1.04	3.25	±0.10
	22	17/0.16	59.40	0.76	1.15	1.04	3.06	±0.10
	24	11/0.16	94.20	0.61	1.15	1.04	2.91	±0.10
	26	7/0.16	150.00	0.48	1.15	1.04	2.78	±0.10

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4
- Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com