



FT-SILB200

Silicone Rubber Braided Tube

General insulating protection for various household appliances, light fitting, machines, electronic instruments, etc



Features

- It's available in two types: Inner fiberglass outside braided silicone rubber(SILB200-N)
Inner silicone rubber outside fiberglass braided(SILB200-W)
- Operating temperature:-55°C-200°C
- RoHS compliant; UL approved
- Good flexibility, arc resistance, corona resistance
- Standard color: white (Other colors upon request)

Dimensions

SILB200-N

Size mm	Internal Diameter (mm)	Average Wall Thickness (mm)			Standard Package M/Spool
		1500V, 2500V	4000V	7000V	
0.5	0.5 ± 0.30	0.20 ± 0.10	0.40 ± 0.10	0.45 ± 0.10	100
1.0	1.0 ± 0.30	0.20 ± 0.10	0.40 ± 0.10	0.45 ± 0.10	100
1.5	1.5 ± 0.30	0.20 ± 0.10	0.40 ± 0.10	0.45 ± 0.10	100
2.0	2.0 ± 0.30	0.20 ± 0.10	0.40 ± 0.10	0.45 ± 0.10	100
2.5	2.5 ± 0.30	0.20 ± 0.10	0.40 ± 0.10	0.50 ± 0.10	100
3.0	3.0 ± 0.35	0.23 ± 0.10	0.40 ± 0.10	0.50 ± 0.10	100
3.5	3.5 ± 0.35	0.23 ± 0.10	0.45 ± 0.10	0.55 ± 0.10	100
4.0	4.0 ± 0.35	0.23 ± 0.10	0.45 ± 0.10	0.55 ± 0.10	100
4.5	4.5 ± 0.35	0.23 ± 0.10	0.45 ± 0.10	0.55 ± 0.10	100
5.0	5.0 ± 0.45	0.30 ± 0.10	0.45 ± 0.10	0.55 ± 0.10	100
6.0	6.0 ± 0.45	0.30 ± 0.10	0.50 ± 0.10	0.60 ± 0.10	100
7.0	7.0 ± 0.60	0.35 ± 0.10	0.50 ± 0.10	0.60 ± 0.10	50
8.0	8.0 ± 0.60	0.35 ± 0.10	0.50 ± 0.10	0.60 ± 0.10	50
9.0	9.0 ± 0.60	0.35 ± 0.10	0.50 ± 0.10	0.60 ± 0.10	50
10.0	10.0 ± 0.80	0.43 ± 0.10	0.60 ± 0.10	0.65 ± 0.10	50
12.0	12.0 ± 0.80	0.43 ± 0.10	0.60 ± 0.10	0.65 ± 0.10	50

SILB200-W

Size (mm)	Normal Dimension			Standard Package (m/spool)
	Internal Diameter (mm)	Wall Thickness (mm)	Average Wall Thickness(mm)	
1.0	1.0 ± 0.30	0.60	0.45 ± 0.05	200
2.0	2.0 ± 0.30	0.60	0.45 ± 0.05	200
3.0	3.0 ± 0.30	0.80	0.50 ± 0.05	100
4.0	4.0 ± 0.30	0.80	0.55 ± 0.05	100
5.0	5.0 ± 0.40	0.80	0.55 ± 0.05	100
6.0	6.0 ± 0.40	1.00	0.60 ± 0.05	100
7.0	7.0 ± 0.40	1.00	0.60 ± 0.05	50
8.0	8.0 ± 0.50	1.00	0.60 ± 0.05	50
9.0	9.0 ± 0.50	1.20	0.60 ± 0.05	50
10.0	10.0 ± 0.50	1.20	0.60 ± 0.05	50