

FT-SHT Skid-Proof Heat Shrinkable Tube

Features:

- Shrink ratio: 2:1
- Working temperature: -55°C~+110°C
- Shrink temperature: Start at 70°C, complete shrink at 105°C
- Durable abrasion, sweat absorption
- Lightweight, flexible, anti-skid
- Avoiding electric shock
- RoHS compliant

Application:

It is widely applied to tennis rackets, badminton rackets, fishing rods, baseball bats, hockey sticks, industrial hand tools, athletic equipment and various handles. It is able to increase friction on smooth surfaces to minimize slipping.



1. Technical Data

Property	Test Method	Standard Required
Tensile Strength (Mpa)	ASTM D412	10.4 Mpa
Longitudinal Elongation (%)	ASTM D412	≤8
Elongation (%)	ISO 1210	200%

2. Dimensions

As supplied		After recovery		Standard Package (m/pcs)
I.D.	Wall thickness	I.D.	Wall thickness	
15	0.45±0.15	8.0	0.85±0.15	1
20	0.50±0.15	11.0	0.90±0.15	1
22	0.50±0.15	12.5	0.90±0.15	1
25	0.50±0.15	14.5	1.00±0.15	1
28	0.50±0.15	15.5	1.00±0.15	1
30	0.60±0.15	17.5	1.20±0.15	1
35	0.60±0.15	20.0	1.20±0.15	1
40	0.60±0.15	23.0	1.20±0.15	1
45	0.65±0.15	25.0	1.25±0.15	1
50	0.65±0.15	28.0	1.25±0.15	1

Remark:

1. Standard color: Black, Red, Yellow, Blue and Green.
2. Special packaging and cutting pieces are available upon requests.