

FT-SIL200H Silicone Rubber Heat Shrinkable Tube

Features:

- Shrink ratio: 1.7:1
- Working temperature: -50℃~+200℃
- Shrink temperature: complete shrink at 220℃
- Oil resistance and chemical resistance
- Flexibility at high and low temperatures without cracking

Application:

It is generally used for cables in medical equipments, home appliances, aerospace, military, automobile manufacturing, electronic components, transformers, motors where extreme physical strength and high temperature are required.



1. Dimensions

As supplied (mm)		After Recovery (mm)		Standard Packing m/spool
I.D.	W.T.	I.D.	W.T.	
1	0.80±0.15	≤0.6	1.10±0.15	200
2	0.80±0.15	≤1.2	1.10±0.15	200
3	0.80±0.15	≤1.8	1.10±0.15	200
4	0.80±0.15	≤2.5	1.10±0.15	200
5	0.80±0.15	≤3.0	1.10±0.15	100
6	0.80±0.15	≤3.8	1.10±0.15	100
7	0.80±0.15	≤4.0	1.10±0.15	100
8	0.80±0.15	≤4.8	1.10±0.15	100
9	0.80±0.15	≤5.0	1.10±0.15	100
10	1.50±0.15	≤6.5	2.50±0.15	50
12	1.50±0.15	≤7.0	2.50±0.15	50
15	1.50±0.15	≤9.0	2.50±0.15	50
20	1.50±0.15	≤13	2.50±0.15	25
25	1.50±0.15	≤15	2.50±0.15	25
30	1.50±0.15	≤18	2.50±0.15	25
35	1.50±0.15	≤20	2.50±0.15	25
40	1.50±0.15	≤25	2.50±0.15	25

Remark:

1. Standard color: Black, Grey.

2. Special colors, packaging and cutting pieces are available upon request.



www.flexwires.com