

# PVC Insulated material

## Style UL2468

### Description:

Conductor: Tinned /Bare copper  
Insulation materials: PVC Insulation  
Rated temperature: 80°C Rated voltage:300V

### Specification:

Type	AWG	Conductor size (No./ mm) ±0.005	Conductor resistance 20°C ( Ω/Km )	Conductor Dia.(mm)	Insulation thickness (mm)		Overall diameter (mm)
					Nom.	Min.	
2468	16	26/0.254	14.60	1.50	0.43	0.35	2.40±0.10× 4.90+/-0.20
	18	41/0.16	23.20	1.17	0.43	0.35	2.04±0.10× 4.23±0.20
	20	21/0.18	36.70	0.95	0.43	0.35	1.80±0.10× 3.70±0.20
	22	7/0.254	59.40	0.77	0.43	0.35	1.62±0.10× 3.34±0.20
	22	17/0.16	59.40	0.76	0.43	0.35	1.62±0.10× 3.34±0.20
	24	11/0.16	94.20	0.61	0.43	0.35	1.47±0.10× 3.04±0.20
	26	7/0.16	150.00	0.48	0.43	0.35	1.34±0.10× 2.78±0.20

### Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4  
- Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



[www.flexwires.com](http://www.flexwires.com)