

PVC Insulated material

Style UL2679

Description:

Conductor: Tinned /Bare copper ;
 Insulation materials: PVC Insulation
 Shield materials:tinned/bare copper or Aluminum foil warp (optional)
 Jacket materials: PVC jacket
 Rated temperature: 60°C Rated voltage:60V

Specification:

Part No.	Conductor				Insulation thickness (mm)		Jacket Thickness (mm)		Overall diameter (mm)		Conductor resistance 20°C (Ω/Km)
	Cores No.	AWG	N0./mm	Dia. mm	Nom.	Min Dia.	Nom.	Min	Nom.	min	
2679	2	26	7/0.16	0.48	0.25	0.98	1.52	1.22	5.40	4.80	150
	2	24	11/0.16	0.61	0.25	1.11	1.52	1.22	5.66	5.06	94.2
	2	22	17/0.16	0.76	0.25	1.26	1.52	1.22	5.96	5.36	59.4
	2	20	26/0.16	0.95	0.25	1.45	1.52	1.22	6.34	5.74	36.7
	3	26	7/0.16	0.48	0.25	0.98	1.52	1.22	5.40	4.80	150
	3	24	11/0.16	0.61	0.25	1.11	1.52	1.22	5.66	5.06	94.2
	3	22	17/0.16	0.76	0.25	1.26	1.52	1.22	5.96	5.36	59.4
	3	20	26/0.16	0.95	0.25	1.45	1.52	1.22	6.34	5.74	36.7
	4	28	7/0.127	0.38	0.25	0.88	1.52	1.22	5.47	4.87	239
	4	26	7/0.16	0.48	0.25	0.98	1.52	1.22	5.70	5.10	150
	5	28	7/0.127	0.38	0.25	0.88	1.52	1.22	5.71	5.11	239
	5	26	7/0.16	0.48	0.25	0.98	1.52	1.22	5.97	5.37	150
	6	28	7/0.127	0.38	0.25	0.88	1.52	1.22	5.93	5.33	239
	6	26	7/0.16	0.48	0.25	0.98	1.52	1.22	6.21	5.61	150
	7	28	7/0.127	0.38	0.25	0.88	1.52	1.22	6.13	5.53	239
	7	26	7/0.16	0.48	0.25	0.98	1.52	1.22	6.43	5.83	150

Note:shield thickness 0.20mm

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 - Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com