

PVC Insulated material

Style UL2733

Description:

Conductor: Tinned /Bare copper ;
 Insulation materials: PVC Insulation
 Shield materials:tinned/bare copper or Aluminum foil warp (optional)
 Jacket materials: PVC jacket
 Rated temperature: 105°C Rated voltage:600V

Specification:

Part No.	Conductor				Insulation thickness (mm)		Jacket Thickness (mm)		Overall diameter (mm)		Conductor resistance 20°C (Ω/Km)
	Cores No.	AW G	N0./mm	Dia. mm	Nom.	Mom Dia.	Nom.	Min	Nom.	Tol.	
2733	2	26	7/0.16	0.50	0.80	2.10	0.40	0.30	5.00	±0.15	150
	2	24	11/0.16	0.61	0.80	2.21	0.40	0.30	5.22	±0.15	94.2
	2	22	17/0.16	0.76	0.80	2.36	0.40	0.30	5.52	±0.15	59.4
	2	20	26/0.16	0.95	0.80	2.55	0.40	0.30	5.90	±0.15	36.7
	2	18	41/0.16	1.18	0.80	2.78	0.40	0.30	6.36	±0.20	23.2
	3	26	7/0.16	0.50	0.80	2.10	0.40	0.30	5.00	±0.15	150
	3	24	11/0.16	0.61	0.80	2.21	0.40	0.30	5.22	±0.15	94.2
	3	22	17/0.16	0.76	0.80	2.36	0.40	0.30	5.52	±0.15	59.4
	3	20	26/0.16	0.95	0.80	2.55	0.40	0.30	5.90	±0.15	36.7
	3	18	41/0.16	1.18	0.80	2.78	0.40	0.30	6.36	±0.20	23.2
	4	28	7/0.127	0.38	0.80	1.98	0.40	0.30	5.37	±0.20	239
	4	26	7/0.16	0.50	0.80	2.10	0.40	0.30	5.65	±0.20	150
	5	28	7/0.127	0.38	0.80	1.98	0.40	0.30	5.91	±0.20	239
	5	26	7/0.16	0.50	0.80	2.10	0.40	0.30	6.22	±0.20	150
	6	28	7/0.127	0.38	0.80	1.98	0.40	0.30	6.40	±0.20	239
	6	26	7/0.16	0.50	0.80	2.10	0.40	0.30	6.74	±0.20	150
	7	28	7/0.127	0.38	0.80	1.98	0.40	0.30	6.85	±0.20	239
	7	26	7/0.16	0.50	0.80	2.10	0.40	0.30	7.22	±0.20	150

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4 – Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com