

ETFE Insulated material

Style UL1670 Wire

Description:

Conductor material Tinned, Silvered or Nickel copper
Rated voltage 150 V
Rated temperature: 150°C
Flame resistance VW-1
RoHS Compliant

Specification:

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Mon	Tol
1670	14	19/0.361	8.96	1.85	0.30	0.27	2.41	±0.10
	16	19/0.287	14.60	1.50	0.30	0.27	2.04	±0.10
	18	19/0.235	23.20	1.18	0.30	0.27	1.78	±0.10
	20	19/0.19	36.70	0.95	0.13	0.10	1.20	±0.10
	22	19/0.15	59.40	0.76	0.13	0.10	1.02	±0.10
	24	7/0.20	94.20	0.60	0.13	0.10	0.85	±0.10
	26	7/0.16	150.00	0.48	0.13	0.10	0.75	±0.10
	28	7/0.127	239.00	0.38	0.13	0.10	0.65	±0.10
	30	1/0.254	361.00	0.254	0.13	0.10	0.52	±0.10

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4
- Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com