

SILICONE RUBBER Insulated material

Style UL3253 Wire

Description:

Conductor: Tinned /Bare copper
Rated voltage 250 V
Rated temperature: 300°C
Flame resistance FT-2
RoHS Compliant

Specification:

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Nom.	Tole.
3253	12	65/0.254	5.64	2.36	0.80	0.69	3.95	±0.15
	14	41/0.254	8.96	1.90	0.80	0.69	3.50	±0.15
	16	7/0.49	14.60	1.50	0.80	0.69	3.10	±0.15
	18	7/0.39	23.20	1.18	0.80	0.69	2.80	±0.15
	20	7/0.30	36.70	0.92	0.80	0.69	2.55	±0.10
	22	7/0.254	59.40	0.76	0.80	0.69	2.35	±0.10
	24	7/0.20	94.20	0.61	0.80	0.69	2.20	±0.10
	26	7/0.16	150.00	0.48	0.80	0.69	2.10	±0.10
	28	7/0.127	239.00	0.38	0.80	0.69	2.00	±0.10
	30	7/0.10	361.00	0.30	0.80	0.69	1.90	±0.10

Order reference:

Colors available: 0-Black, 1-Brown, 2-Red, 3-Orange, 4-Yellow, 5-Green, 6-Blue, 7-Violet, 8-Grey, 9-White, 5/4
– Green W/ Yellow

Striping: Longitudinal and Parallel Stripes Available Per Request

Delivery: All Stocked Items Available for Immediate Shipment, 8 Week Lead Time for Non-stocked Items

Package: Stocked in Spools, Barrel Pack Available Per Request

Wire Processing: Cut, Strip, and Tinning Available



www.flexwires.com